

# HC 301 PP Tape

## PRODUCT DATA SHEET



### CONSTRUCTION

Substrate: 1.5-mil BOPP  
Adhesive: 1.5-mil Solvent Acrylic  
Liner: None

### FEATURES

- Flexible duct closure tape
- High tack adhesive
- Bonds well to all types of flexible and rigid ducts as well as all types of connectors
- Hand tearable
- Performs well in challenging environmental conditions
- UL181 B-FX listed
- Available in silver, black or clear

### TYPICAL PROPERTIES

Test	Typical Values (English)	Typical Values (metric)	Test Method
Total Thickness	0.0031-in	0.0787-mm	PSTC-133
Peel Adhesion to Stainless Steel	45-oz/in	4.9-N/cm	PSTC-101
Tensile Strength	32-lbs/in	56-N/cm	PSTC-131
Surface Burning Characteristics	Flame $\leq$ 5 Smoke $\leq$ 5	Flame $\leq$ 5 Smoke $\leq$ 5	UL 723* ASTM E 84

*\*Tested in accordance with UL 723*

### APPLICATION

Application surface must be clean, dry and free of contaminants. Apply pressure with plastic squeegee.

### SHELF LIFE & STORAGE

Under ideal storage conditions of 60°F to 80°F and low humidity, shelf life is one year from date of purchase.

### STANDARD CONFIGURATIONS & PACKAGING (CUSTOM CONFIGURATIONS & PACKAGING AVAILABLE UPON REQUEST)

Roll Width	Roll Length	Rolls/Carton	Cartons/Pallet
2-in	120-yds	24	27
3-in	120-yds	16	27

*Physical and performance values and characteristics shown above are obtained through recommended test procedures. The above values do not represent a guarantee of product performance. Values represent nominal and average values; individual roll values may vary from average values indicated on the data sheet. User is responsible for determining suitability and fitness for use. Revision 9.8.2009 11:37.*