

# HC 601 Cork Tape

## PRODUCT DATA SHEET



### CONSTRUCTION

Material: Cork/Bitumen  
Liner: 40-lb Silicone Coated Glassine

### FEATURES

- Composed of cork, butyl rubber and modified asphalt
- Suitable for wrapping hot and cold pipe, fittings and tubing
- Prevents condensation
- Prevents heat gain or loss
- Prevents frost from forming on chilled water refrigeration tubing
- Black

### TYPICAL PROPERTIES

Test	Typical Values (English)	Typical Values (metric)	Test Method
Thickness	0.125-in	3.175-mm	PSTC-133
Elongation	100.0%	100.0%	PSTC-131
Specific Gravity	1.1	1.1	HC Internal
Water Absorption	Max 5% by weight	Max 5% by weight	ASTM D-1056

### APPLICATION

Application surface must be clean, dry and free of contaminants.

### SHELF LIFE & STORAGE

Under ideal storage conditions of 60°F to 80°F and low humidity, shelf life is one year from date of purchase.

### STANDARD CONFIGURATIONS & PACKAGING (CUSTOM CONFIGURATIONS & PACKAGING AVAILABLE UPON REQUEST)

Roll Width	Roll Length	Rolls/Carton	Cartons/Pallet
0.75-in	30-ft	64	27
1-in	30-ft	48	27
2-in	30-ft	24	27
3-in	30-ft	16	27

*Physical and performance values and characteristics shown above are obtained through recommended test procedures. The above values do not represent a guarantee of product performance. Values represent nominal and average values; individual roll values may vary from average values indicated on the data sheet. User is responsible for determining suitability and fitness for use. Revision 8.27.2009 12:17.*