

# HC 302 PP Tape

## PRODUCT DATA SHEET



### CONSTRUCTION

Substrate: PSK (Poly Scrim Kraft)  
Adhesive: Rubber  
Liner: 60-lb Silicone Coated Kraft



### FEATURES

- An aggressive rubber adhesive system
- Bonds tightly and permanently to FSK faced metal building insulation
- Performs well over a wide range of environmental conditions
- White outer surface matches PSK facings

### TYPICAL PROPERTIES

Test	Typical Values (English)	Typical Values (metric)	Test Method
Thickness	0.0068-in	0.1727-mm	PSTC-133
Peel Adhesion to Stainless Steel	72-oz/in	7.9-N/cm	PSTC-101
Tensile Strength	42-lbs/in	74-N/cm	PSTC-131
Elongation	1.0%	1.0%	PSTC-131
Surface Burning Characteristics	10 Flame 15 Smoke	10 Flame 15 Smoke	UL 723* ASTM E 84

*\*Tested in accordance with UL 723*

### APPLICATION

Application surface must be clean, dry and free of contaminants. Apply pressure with plastic squeegee.

### SHELF LIFE & STORAGE

Under ideal storage conditions of 60°F to 80°F and low humidity, shelf life is one year from date of purchase.

### STANDARD CONFIGURATIONS & PACKAGING (CUSTOM CONFIGURATIONS & PACKAGING AVAILABLE UPON REQUEST)

Roll Width	Roll Length	Rolls/Carton	Cartons/Pallet
3-in	150-ft	16	27

*Physical and performance values and characteristics shown above are obtained through recommended test procedures. The above values do not represent a guarantee of product performance. Values represent nominal and average values; individual roll values may vary from average values indicated on the data sheet. User is responsible for determining suitability and fitness for use. Revision 1.8.2010 14:32.*