

# HC 405 PVC Tape

## PRODUCT DATA SHEET



### CONSTRUCTION

Substrate: 10-mil PVC  
Adhesive: Rubber  
Liner: None

### FEATURES

- Rubber based adhesive
- Protects pipe joints conduit coupling
- Can be used in direct buried applications
- Resistant to water, oil, acids and alkaline
- White

### TYPICAL PROPERTIES

Test	Typical Values (English)	Typical Values (metric)	Test Method
Thickness	0.010-in	0.254-mm	PSTC-133
Peel Adhesion to Stainless Steel	12-oz/in	1.3-N/cm	PSTC-101
Tensile Strength	20-lbs/in	35-N/cm	PSTC-131
Elongation	250%	250%	PSTC-131

### APPLICATION

Application surface must be clean, dry and free of contaminants.

### SHELF LIFE & STORAGE

Under ideal storage conditions of 60°F to 80°F and low humidity, shelf life is one year from date of purchase.

### STANDARD CONFIGURATIONS & PACKAGING (CUSTOM CONFIGURATIONS & PACKAGING AVAILABLE UPON REQUEST)

Roll Width	Roll Length	Rolls/Carton	Cartons/Pallet
1½-in	100-ft	32	27
2-in	100-ft	24	27

*Physical and performance values and characteristics shown above are obtained through recommended test procedures. The above values do not represent a guarantee of product performance. Values represent nominal and average values; individual roll values may vary from average values indicated on the data sheet. User is responsible for determining suitability and fitness for use. Revision 1.12.2010 08:19.*