

HC 402 PVC Tape

PRODUCT DATA SHEET



CONSTRUCTION

Substrate: 10-mil PVC
Adhesive: Rubber
Liner: None

FEATURES

- Rubber based adhesive
- Bonds well to PVC fittings and pipe
- Performs well in challenging environmental conditions
- Resistant to many chemicals
- White, other colors available upon request

TYPICAL PROPERTIES

Test	Typical Values (English)	Typical Values (metric)	Test Method
Thickness	0.010-in	0.254-mm	PSTC-133
Peel Adhesion to Stainless Steel	20-oz/in	2.2-N/cm	PSTC-101
Tensile Strength	20-lbs/in	35-N/cm	PSTC-131
Elongation	275%	275%	PSTC-131

APPLICATION

Application surface must be clean, dry and free of contaminants.

SHELF LIFE & STORAGE

Under ideal storage conditions of 60°F to 80°F and low humidity, shelf life is one year from date of purchase.

STANDARD CONFIGURATIONS & PACKAGING (CUSTOM CONFIGURATIONS & PACKAGING AVAILABLE UPON REQUEST)

Roll Width	Roll Length	Rolls/Carton	Cartons/Pallet
3-in	150-ft	16	27

Physical and performance values and characteristics shown above are obtained through recommended test procedures. The above values do not represent a guarantee of product performance. Values represent nominal and average values; individual roll values may vary from average values indicated on the data sheet. User is responsible for determining suitability and fitness for use. Revision 8.27.2009 11:39.